
REPORT No. 315

AERODYNAMIC CHARACTERISTICS OF AIRFOILS—VI

CONTINUATION OF REPORTS Nos. 93, 124, 182, 244, and 286

By

**NATIONAL ADVISORY COMMITTEE
FOR AERONAUTICS**

TABLE OF CONTENTS

	Page
Introduction.....	213
Transformation constants.....	213
Chart index.....	215
Index of abbreviations.....	215
Group index.....	216
Alphabetical index.....	217
Airfoil sections.....	218-242
United States sections.....	218-220
German sections.....	220-227
French sections.....	227-232
Belgium sections.....	233-235
Italian sections.....	235-242
Charts Nos. 21, 22, 23, 24.....	243-246

REPORT No. 315

AERODYNAMIC CHARACTERISTICS OF AIRFOILS—VI

CONTINUATION OF REPORTS NOS. 93, 124, 182, 244, AND 286

By NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

INTRODUCTION

This collection of data on airfoils has been made from the published reports of a number of the leading aerodynamic laboratories of this country and Europe.¹ The information which was originally expressed according to the different customs of the several laboratories is here presented in a uniform series of charts and tables suitable for the use of designing engineers and for purposes of general reference.

It is a well-known fact that the results obtained in different laboratories, because of their individual methods of testing, are not strictly comparable even if proper scale corrections for size of model and speed of test are supplied. It is, therefore, unwise to compare too closely the coefficients of two wing sections tested in different laboratories. Tests of different wing sections from the same source, however, may be relied on to give true relative values.

The absolute system of coefficients has been used, since it is thought by the National Advisory Committee for Aeronautics that this system is the one most suited for international use and yet it is one from which a desired transformation can be easily made. For this purpose a set of transformation constants is given.

Each airfoil section is given a reference number, and the test data are presented in the form of curves from which the coefficients can be read with sufficient accuracy for designing purposes. The dimensions of the profile of each section are given at various stations along the chord in per cent of the chord length, the latter also serving as the datum line. The shape of the section is also shown with reasonable accuracy in order to enable one to more clearly visualize the section under consideration, the outside of the heavy line representing the profile.

The authority for the results here presented is given as the name of the laboratory at which the experiments were conducted, as explained under abbreviations, with the size of model, wind velocity, and year of test.

TRANSFORMATION CONSTANTS

For the convenience of those who prefer to use a system of units other than the absolute system, there is given below a table of transformation constants based on the standard condition adopted by the National Advisory Committee for Aeronautics of—

Temperature	= 15° C	= 59° F.
Pressure	= 760 mm Hg	= 29.92 in. Hg.
Humidity	= 0	
Gravity	= 9.80665 m/s ²	= 32.1740 ft./sec. ²

thus giving values of specific weight of air

$$W = 1.2255 \text{ kg/m}^3 = 0.07651 \text{ lb./cu. ft.}$$

¹ A previous collection of airfoil sections numbered 1 to 759 and Charts 1 to 20 may be found in N. A. C. A. Reports Nos. 93, 124, 182, 244, and 286.

and of density

$\rho = 0.12497 \text{ kg-m}^{-4}\text{s}^2$ in the French engineering or kilogram, meter, second system.
Or

$\rho = 0.002378 \text{ lb.-ft.}^{-4}\text{sec.}^2$	in the English or pound, foot, second system.
In absolute units	$P = CV^2 \rho / 2$
In kg/m^2 (m/s)	$P = .0625 CV^2$
In kg/m^2 (km/h)	$P = .004822 CV^2$
In lb./sq. ft. (ft./sec.)	$P = .001189 CV^2$
In lb./sq. ft. (mi./hr.)	$P = .002558 CV^2$

(Note that these constants are half as large as those used in Reports Nos. 93 and 124 and that the absolute coefficients used in this report are twice as large as the old coefficients. See Report No. 240 regarding change in absolute coefficients.)

INDEX

Four separate types of indexes are given—chart indexes which make it possible for a designer to select the wing section most suitable for the particular design in which he is interested; a group index which is arranged by countries and laboratories at which tests were conducted, each section also being designated by a reference number; an index of abbreviations, used on the characteristic sheets, to indicate the laboratories at which the tests were made; and an alphabetical index.

CHART INDEX

In order that the designer may easily pick out a wing section which is suited to the type of airplane on which he is working, four index charts are given which classify the wings according to their aerodynamic and structural properties. In the charts of this report a lower-case letter is placed adjacent to the reference number giving Vl values, so that a comparison can be made without referring to the individual drawings. In this value V represents the wind velocity in feet per second and l a linear dimension, the chord length in feet.

In chart No. 21 the minimum drag C_D , is plotted against the L/D at one-fourth the maximum lift C_L . This chart should be used in choosing a wing section for a high-speed airplane, the wing sections being more suited for this use the farther they are from the lower left-hand corner.

In chart No. 22 the mean spar depth is plotted against the maximum lift C_L , in order to show the possible strength and lightness of the wing structure. The higher the maximum lift coefficient is, the smaller will be the wing area and the lighter the structural weight, and in the same way the greater the depth of the spars the lighter will be their weight, so that the sections the greatest distance from the lower left-hand corner will give the lightest and strongest wings. The "mean spar depth" is obtained by assuming the spars to be located, respectively, at 15 and 60 per cent of the chord, and by dividing the sum of their thicknesses, in per cent of chord length at these points, by 2.

In chart No. 23 the maximum L/D is plotted against the maximum lift C_L , which is of use in choosing the wing section for a slow and efficient airplane. In the same way as before the sections farthest from the lower left-hand corner are the best for this purpose.

In chart No. 24 the L/D at two-thirds the maximum lift C_L , is plotted against the maximum lift C_L . This chart can be used for choosing a section that will give an efficient climb or a long range at cruising speed. The best sections for this purpose will be farthest from the lower left-hand corner of the chart.

CHART INDEX

	Page
Chart No. 21. Minimum drag C_D , plotted against L/D at one-fourth the maximum lift C_L -----	243
Chart No. 22. Mean spar depth plotted against the maximum lift C_L -----	244
Chart No. 23. Maximum L/D plotted against maximum lift C_L -----	245
Chart No. 24. L/D at two-thirds the maximum lift C_L , plotted against the maximum lift C_L -----	246

INDEX OF ABBREVIATIONS

Name of laboratory at which tests were made	Abbreviations used on figures
Langley Memorial Aeronautical Laboratory of the National Advisory Committee for Aeronautics, U. S. A.	L. M. A. L.
Washington Navy Yard, U. S. A.	W. N. Y.
Engineering Division, McCook Field, U. S. A.	McC. F.
Ergebnisse der Aerodynamischen Versuchsanstalt zu Göttingen, Germany	Göttingen.
Service Technique de l'Aéronautique, France	S. T. Aé.
Laboratoire Aerotechnique de Rhode St. Genese-Bruxelles, Belgium	Rhode St. Genese.
Instituto Sperimentale Aeronautico, Italy	I. S. A.


GROUP INDEX

Airfoil	Wind tunnel where tested	Report reference number	Airfoil	Wind tunnel where tested	Report reference number
UNITED STATES					
U. S. N. P. S. 1	L. M. A. L.	760	St. Cyr 162 (Royer)	S. T. Aé. Lab.	810
U. S. N. P. S. 2	do	761	St. Cyr 170 (Royer)	do	811
U. S. N. P. S. 3	do	762	St. Cyr 174 (Royer)	do	812
U. S. N. P. S. 4	do	763	St. Cyr 233 (Bartel 37-Ib)	do	813
U. S. N. P. S. 5	do	764	St. Cyr 235 (Bartel 37-Ic)	do	814
U. S. N. P. S. 6	do	765	St. Cyr 237 (Bartel 15-Ic)	do	815
Martin M-I	W. N. Y.	766	St. Cyr 239 (Bartel 37-IIa)	do	816
Martin M-II	do	767	St. Cyr 240 (Bartel 37-IIb)	do	817
Martin M-III	do	768	St. Cyr 242 (Bartel 57-IIc)	do	818
R-3 (Root section)	McC. F	769	St. Cyr 243 (Bartel 37-IIIc)	do	819
U. S. A. 45M	do	770			
GERMANY					
Göttingen 359	Göttingen	771	Rhode St. Genese 1	Rhode St. Genese	820
Göttingen 361	do	772	Rhode St. Genese 2	do	821
Göttingen 362	do	773	Rhode St. Genese 16	do	822
Göttingen 368	do	774	Rhode St. Genese 17	do	823
Göttingen 369	do	775	Rhode St. Genese 19	do	824
Göttingen 371	do	776	Rhode St. Genese 26	do	825
Göttingen 372	do	777	Rhode St. Genese 29	do	826
Göttingen 373	do	778	Rhode St. Genese 31	do	827
Göttingen 374	do	779	Rhode St. Genese 33	do	828
Göttingen 375	do	780	Rhode St. Genese 35	do	829
Göttingen 377	do	781	Rhode St. Genese 37	do	830
Göttingen 392	do	782			
Göttingen 397	do	783			
Göttingen 399	do	784	I. S. A. 334	I. S. A.	831
Göttingen 401	do	785	I. S. A. 390	do	832
Göttingen 402	do	786	I. S. A. 472	do	833
Göttingen 403	do	787	I. S. A. 500	do	834
Göttingen 408	do	788	I. S. A. 501	do	835
Göttingen 417	do	789	I. S. A. 502	do	836
Göttingen 428	do	790	I. S. A. 507	do	837
Göttingen 437	do	791	I. S. A. 605	do	838
Göttingen 438	do	792	I. S. A. 668	do	839
Göttingen 439	do	793	I. S. A. 693	do	840
Göttingen 442	do	794	I. S. A. 695	do	841
Göttingen 443	do	795	I. S. A. 768	do	842
Göttingen 444	do	796	I. S. A. 776	do	843
Göttingen 445	do	797	I. S. A. 801	do	844
			I. S. A. 803	do	845
			I. S. A. 804	do	846
			I. S. A. 805	do	847
Eiffel 359 (Nieuport Astra)	S. T. Aé. Lab.	798	I. S. A. 806	do	848
Eiffel 386 (S. T. Aé.)	do	799	I. S. A. 807	do	849
Eiffel 387 (S. T. Aé.)	do	800	I. S. A. 809	do	850
Eiffel 402 (Pescara)	do	801	I. S. A. 812	do	851
Eiffel 429 (Lachassagne)	do	802	I. S. A. 820	do	852
Eiffel 432 (Lachassagne)	do	803	I. S. A. 821	do	853
Eiffel 433a (Chalambel)	do	804	I. S. A. 829	do	854
Eiffel 438 (Lachassagne)	do	805	I. S. A. 858	do	855
St. Cyr 152 (Royer)	do	806	I. S. A. 881a	do	856
St. Cyr 153 (Royer)	do	807	I. S. A. 881b	do	857
St. Cyr 156 (Royer)	do	808	I. S. A. 881c	do	858
St. Cyr 157 (Royer)	do	809	I. S. A. 911	do	859


ALPHABETICAL INDEX

Airfoil	Report reference number	Airfoil	Report reference number
Eiffel 359 (Nieuport Astra)	798	I. S. A. 804	846
Eiffel 386 (S. T. A6.)	799	I. S. A. 805	847
Eiffel 387 (S. T. A6.)	800	I. S. A. 806	848
Eiffel 402 (Pescara)	801	I. S. A. 807	849
Eiffel 429 (Lachassagne)	802	I. S. A. 809	850
Eiffel 432 (Lachassagne)	803	I. S. A. 812	851
Eiffel 433a (Chalambel)	804	I. S. A. 820	852
Eiffel 433 (Lachassagne)	805	I. S. A. 821	853
Göttingen 359	771	I. S. A. 829	854
Göttingen 361	772	I. S. A. 858	855
Göttingen 362	773	I. S. A. 881a	856
Göttingen 363	774	I. S. A. 881b	857
Göttingen 369	775	I. S. A. 881c	858
Göttingen 371	776	I. S. A. 911	859
Göttingen 372	777	Martin M-I	766
Göttingen 373	778	Martin M-II	767
Göttingen 374	779	Martin M-III	768
Göttingen 375	780	R-3 (Root Section)	769
Göttingen 377	781	Rhode St. Genese 1	820
Göttingen 392	782	Rhode St. Genese 2	821
Göttingen 397	783	Rhode St. Genese 16	822
Göttingen 399	784	Rhode St. Genese 17	823
Göttingen 401	785	Rhode St. Genese 19	824
Göttingen 402	786	Rhode St. Genese 26	825
Göttingen 403	787	Rhode St. Genese 29	826
Göttingen 408	788	Rhode St. Genese 31	827
Göttingen 417	789	Rhode St. Genese 33	828
Göttingen 428	790	Rhode St. Genese 35	829
Göttingen 437	791	Rhode St. Genese 37	830
Göttingen 438	792	St. Cyr 152 (Royer)	806
Göttingen 439	793	St. Cyr 153 (Royer)	807
Göttingen 442	794	St. Cyr 156 (Royer)	808
Göttingen 443	795	St. Cyr 157 (Royer)	809
Göttingen 444	796	St. Cyr 162 (Royer)	810
Göttingen 445	797	St. Cyr 170 (Royer)	811
I. S. A. 334	831	St. Cyr 174 (Royer)	812
I. S. A. 390	832	St. Cyr 233 (Bartel 37-IIb)	813
I. S. A. 472	833	St. Cyr 235 (Bartel 37-Ic)	814
I. S. A. 500	834	St. Cyr 237 (Bartel 15-Ic)	815
I. S. A. 501	835	St. Cyr 239 (Bartel 37-IIa)	816
I. S. A. 502	836	St. Cyr 240 (Bartel 37-IIb)	817
I. S. A. 507	837	St. Cyr 242 (Bartel 57-IIc)	818
I. S. A. 605	838	St. Cyr 243 (Bartel 37-IIIc)	819
I. S. A. 663	839	U. S. A. 45M	770
I. S. A. 693	840	U. S. N. P. S. 1	760
I. S. A. 695	841	U. S. N. P. S. 2	761
I. S. A. 768	842	U. S. N. P. S. 3	762
I. S. A. 776	843	U. S. N. P. S. 4	763
I. S. A. 801	844	U. S. N. P. S. 5	764
I. S. A. 803	845	U. S. N. P. S. 6	765


REFERENCE NO. 760




REFERENCE NO. 761




REFERENCE NO. 762




REFERENCE NO. 763




REFERENCE NO. 764




REFERENCE NO. 765




REFERENCE NO. 766




REFERENCE NO. 767




REFERENCE NO. 768




REFERENCE NO. 769




REFERENCE NO. 770




REFERENCE NO. 771




REFERENCE NO. 772




REFERENCE NO. 773




REFERENCE NO. 774




REFERENCE NO. 775




REFERENCE NO. 776




REFERENCE NO. 777




REFERENCE NO. 778




REFERENCE NO. 779




REFERENCE NO. 780




REFERENCE NO. 781




REFERENCE NO. 782




REFERENCE NO. 783




REFERENCE NO. 784




REFERENCE NO. 785




REFERENCE NO. 786




REFERENCE NO. 787




REFERENCE NO. 788




REFERENCE NO. 789




REFERENCE NO. 790




REFERENCE NO. 791




REFERENCE NO. 792




REFERENCE NO. 793




REFERENCE NO. 794




REFERENCE NO. 795




REFERENCE NO. 736




REFERENCE NO. 737




REFERENCE NO. 738




REFERENCE NO. 739




REFERENCE NO. 800




REFERENCE NO. 801



REFERENCE NO. 802




REFERENCE NO. 803




AERODYNAMIC CHARACTERISTICS OF AIRFOILS—VI

229


REFERENCE NO. 804




REFERENCE NO. 805




REFERENCE NO. 806




REFERENCE NO. 807




REFERENCE NO. 808




REFERENCE NO. 809




REFERENCE NO. 810




REFERENCE NO. 811




REFERENCE NO. 612




REFERENCE NO. 615




REFERENCE NO. 614




REFERENCE NO. 615




REFERENCE NO. 816




REFERENCE NO. 817



REFERENCE NO. 818




REFERENCE NO. 819




AERODYNAMIC CHARACTERISTICS OF AIRFOILS—VI

233


REFERENCE NO. 620




REFERENCE NO. 621




REFERENCE NO. 622




REFERENCE NO. 623




REFERENCE NO. 824




REFERENCE NO. 825




REFERENCE NO. 826




REFERENCE NO. 828




REFERENCE NO. 829




REFERENCE NO. 830




REFERENCE NO. 831




REFERENCE NO. 832




REFERENCE NO. 833




REFERENCE NO. 834




REFERENCE NO. 835




REFERENCE NO. 636




REFERENCE NO. 637




REFERENCE NO. 638




REFERENCE NO. 639




REFERENCE NO. 840



REFERENCE NO. 843



REFERENCE NO. 845



Reference No. 840
Center of Pressure in % of Chord from leading Edge
0 2 4 6 8 10 12 14 16 18 20 22
0 0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50
Percent of Chord 20
0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50
L/D
 C_L
 C_D
Ratio of Lift to Drag
0 10 20 30 40 50 60 70 80 90 100
N.A.C.A.
0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50
Angle of Attack in degrees.

Name of section: I. S. A. 758
Size of model: 38.37" x 6.562"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1930


Reference No. 843
Center of Pressure in % of Chord from leading Edge
0 2 4 6 8 10 12 14 16 18 20 22
0 0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50
Percent of Chord 20
0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50
L/D
 C_L
 C_D
Ratio of Lift to Drag
0 10 20 30 40 50 60 70 80 90 100
N.A.C.A.
0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50
Angle of Attack in degrees.

Name of section: I. S. A. 885
Size of model: 38.36" x 4.724"
Wind velocity: 59 ft./sec.
Where tested: I. S. A. Date: 1930


Reference No. 845
Center of Pressure in % of Chord from leading Edge
0 2 4 6 8 10 12 14 16 18 20 22
0 0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50
Percent of Chord 20
0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50
L/D
 C_L
 C_D
Ratio of Lift to Drag
0 10 20 30 40 50 60 70 80 90 100
N.A.C.A.
0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50
Angle of Attack in degrees.

Name of section: I. S. A. 776
Size of model: 38.37" x 6.562"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1930


REFERENCE NO. 844




REFERENCE NO. 845




REFERENCE NO. 846




REFERENCE NO. 847




REFERENCE NO. 848




REFERENCE NO. 848



REFERENCE NO. 850



REFERENCE NO. 851







AERODYNAMIC CHARACTERISTICS OF AIRFOILS—VI

241

REFERENCE NO. 853 Percent of Chord N.A.C.A.

REFERENCE NO. 853 Percent of Chord N.A.C.A.



Angle of Attack in Degrees.


Angle of Attack in Degrees.

Name of section: I. S. A. 853
Size of model: 23.50" x 5.243"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1920


Name of section: I. S. A. 853
Size of model: 23.50" x 5.243"
Wind velocity: 65.6 ft./sec.
Where tested: I. S. A. Date: 1920

REPORT NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS


REFERENCE NO. 856



REFERENCE NO. 857



REFERENCE NO. 858



REFERENCE NO. 859

